Dynapac CP2100W



Pneumatic rollers



Technical data

Masses	
Operating mass (incl. ROPS)	9450 kg
Mass with max. ballast	21000 kg
Mass with wet sand ballast	14150 kg

Traction	
Speed low	9 km/h
Speed high	23 km/h
Speed high (EEC countries)	20 km/h

***	Compaction	
	Rolling width	2265 mm
	Tyre overlap	42 mm
	Wheel loads, without ballast	1350 kg
	Wheel loads, with wet sand ballast	2020 kg
	Wheel loads, with max. ballast	3000 kg
	Tyre pressure, min	250 kPa
	Tyre pressure, max	850 kPa
	Tyre type (smooth)	14/70 R20
	Water spray system, type	Pressurized
	Water spray system, tank capacity	415
	Water spray system, spray nozzle	one per tyre
	Ballast volume	2.20 m ³

Engine	
Manufacturer/Model	Cummins QSB 3.8 (Tier 4F)
Rated power, SAE J1995	89 kW (118 hp) @ 2200 rpm
Туре	Water cooled turbo Diesel
Fuel tank capacity	210
Electrical system	24V

Engine	
Manufacturer/Model	Cummins QSB 3.8 (Tier 4F)
Rated power, SAE J1995	97 kW (130 hp) @ 2200 rpm

Engine	
Manufacturer/Model	Cummins QSB 3.3 (Tier 3A)
Rated power, SAE J1995	74 kW (99 hp) @ 2200 rpm

Hydraulic syste	Hydraulic system	
Driving	Axial piston pump with variable displacement. Axial piston motors (2) with variable displacement.	
Steering	Axial piston pump with variable displacement.	
Service brake	2 multidisc brakes on rear wheels activated by pedal.	
Parking/ Emergency brake	Failsafe multidisc brakes in both gear boxes.	

Dynapac CP2100W



Pneumatic rollers

Technical data



